

565 Soil Guard™



- High traction mat made to withstand the toughest conditions due to its superior rubber compound.
- Stops dirt, grit and grime outside the doorway.
- Bevelled edges for safety and easy cart access.
- Non shifting grip pattern underneath.
- Outdoor entrances - Heavy foot traffic area.
- Hose off with water and hang to dry.



565 Soil Guard™

PRODUCT SPECIFICATIONS			
Designation	Dust Control Matting		
Type	Non-absorbent / scrape rubber mat		
Description	High traction mat, bevelled edges, non shifting grip pattern underneath.		
Material	Natural rubber compound		
Process	Compression moulding		
Category	Outdoor Non-absorbent - Rubber classics		
Recommended use	Outdoor - heavy foot traffic areas		
Colours	Black		
Weight	7,5 kg/m ²		
Thickness	7 mm		
Standard sizes	90 cm x 150 cm		
Custom sizes			
Special remarks			
PRODUCT TESTING			
Tests	Norms	Results	
Abrasion resistance	ASTM D3884	3.30% weight loss	
Colour fastness to light	AATCC 16E		
Accelerated wear test by sim floor machine	U.S.		
Accelerated soiling	U.S.		
Anti-slip	DIN51130 BGR181		
Water retention	U.S.		
Hardness	U.S.		
Coefficient of friction	ASTM C1028-96	0,78	
FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability	<ul style="list-style-type: none"> • Recyclable material • REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals 		