

# 193 Brilliantstep™ Standard



- This high quality multi-functional dust control mat not only cleans and dries shoes, to prevent dirt and moisture getting tracked in to facilities; it also provides an excellent opportunity to promote a brand or company name because most people primarily look to the floor.
- Superior colours fastness is ensured, in accordance with DIN54006.
- 16 standard PMS colours are offered, whereby any other colour can be matched.
- BrilliantStep™ offers a state-of-the-art technology that even allows 3-dimensional effects, fine lines and color shading, for each mat to have its truly individual image.
- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

|    |    |    |    |
|----|----|----|----|
| 1  | 2  | 3  | 4  |
| 5  | 6  | 7  | 8  |
| 9  | 10 | 11 | 12 |
| 13 | 14 | 15 | 16 |

# 193 Brilliantstep™ Standard

| PRODUCT SPECIFICATIONS                     |  |  |   |
|--|--|--|---|
| Designation                                |  | Dust Control Matting   |   |
| Description                                |  | Absorbent carpet mat with printed design   |   |
| Material                                   |  |  |   |
|  | Top  | Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarn<br>405 grams of yarn per m²  |   |
|  | Backing  | Vinyl backing with smooth finish.  |   |
| Process                                    |  | Tufted   |   |
| Category                                   |  | Indoor absorbent   |   |
| Recommended use                            |  | Indoor - light traffic conditions  |   |
| Colours                                    |  | Pallet of 16 attractive colours  |   |
| Weight                                     |  | 2.7 kg/m²  |   |
| Thickness                                  |  | 6 mm   |   |
| Standard sizes                             |  | 60 cm x 90 cm<br>90 cm x 120 cm<br>90 cm x 150 cm<br>90 cm x 300 cm<br>120 cm x 180 cm   |   |
| Custom sizes                               |  | 90 cm per linear meter<br>120 cm per linear meter  |   |
| Special remarks                            |  |  |   |
| PRODUCT TESTING                            |  |  |   |
| Tests                                      |  | Norms  | Results   |
| Abrasion resistance                        |  | ASTM D3884   |   |
| Colour fastness to light                   |  | AATCC 16E  |   |
| Accelerated wear test by sim floor machine |  | U.S.   |   |
| Accelerated soiling                        |  | U.S.   |   |
| Anti-slip                                  |  | DIN51130<br>BGR181   |   |
| Water retention                            |  | U.S.   | 3 l/m²  |
| Sanitary epidemiologic test                |  | GN 2.1.6.1338-03 MCL<br>GN 2.1.6.2309-07 OBUV  | Pass - Certificate no.<br>77.01.16.229.P.044984.07.09 |
| Graves tear strength                       |  |  |   |
| Hardness                                   |  |  |   |
| Elongation                                 |  |  |   |
| FIRE TESTING                               |  |  |   |
|  | Surface Flammability                               | ASTM D2859   | Pass  |
|  | Classification of the reaction to fire performance | EN ISO 9239-1  | Efl - S1  |
| Sustainability                             |  | <ul style="list-style-type: none"><li>• Recyclable material</li><li>• REACH compliant ( Registration, Evaluation, Authorization and restrictions of Chemicals)</li><li>• Contributes to cleaner environment by reducing need of cleaning chemicals</li></ul> |   |