599 Oct-O-Flex™ Bevelled



- The mat is designed to function at the immediate entrance, primarily as a scraper mat to stop dirt, grit and grime outside the doorway.
- No bumpy surface, ideal for carts, wheel chairs etc.
- Friendly for elderly or disabled people.
- Strong product, suitable for heavy foot traffic.
- Small drainage holes diameter, compliant with EU norm for public entrances.
- Withstands weather extremes of all seasons and the heaviest of foot traffic.
- Open structure and raised knobs permit water to drain through, leaving a clean and dry surface.
- Excellent adherence and adapts to any surface.
- Natural rubber, environmentally friendly.
- Hose off with water.



599 Oct-O-Flex™ Bevelled

		PRODUCT SPECIFICATIONS	
Designation	Dust Control Matting		
Туре	Non-absorbent/ scrape rubber mat		
Description	Octogonal ring design with open construction		
Material	Natural rubber compound		
Process	Compression moulding		
Category	Outdoor Non-absorbent - Rubber classics		
Recommended use	Outdoor - medium to heavy foot traffic		
Colours	Black		
Weight	9,8 kg/m²		
Thickness	12,5 mm		
Standard sizes	70 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm		
Custom sizes			
Special remarks	Suitable for use under extreme weather Small holes diameter 14 mm, compliant with EU norm for public entrances		
		PRODUCT TESTING	
Tests		Norms	Results
Abrasion resistance		ASTM D3884	
Colour fastness to light		AATCC 16E	
Accelerated wear test by sim floor machine		U.S.	
Accelerated soiling		U.S.	
Anti-slip		DIN51130 BGR181	
Water retention		U.S	
Hardness		U.S	
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.251.P.044985.07.09
		FIRE TESTING	
	Surface Flammability	ASTM D2859	
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability		 Recyclable material REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) Contributes to cleaner environment by reducing need of cleaning chemicals 	

Supermaty.pl