599 Oct-O-Flex™







- Small holes diameter 14 mm, compliant with EU norm for public entrances, this rubber mat is designed to function at the immediate entrance, primarily as a scraper mat to stop dirt, grit and grime outside the doorway.
- No bumpy surface, ideal for carts, wheel chairs etc.
- Also available with molded rubber ramps.
- Its superior rubber compounds is made to withstand weather extremes and the heaviest of foot traffic
- Raised knobs underneath allow excellent drainage, leaving a clean and dry surface.
- Outdoor entrances - Heavy foot traffic areas
- Custom sizes available.
- Hose off with water.

599 Oct-O-Flex™

PRODUCT SPECIFICATIONS	
Designation	Dust Control Matting
Type	Non-absorbent/ scrape rubber mat
Description	Octogonal ring design with open construction
Material	Natural rubber compound
Process	Compression moulding
Category	Outdoor Non absorbent - Rubber classics
Recommended use	Outdoor - medium to heavy foot traffic
Colours	Black
Weight	10,3 kg/m²
Thickness	12,5 mm
Standard sizes	75 cm x 100 cm 100 cm x 150 cm
Custom sizes	Per m²
Special remarks	Suitable for use under extreme weather Accessories: Connectors Small holes diameter 14 mm, compliant with EU norm for public entrances

PRODUCT TESTING		
Tests	**Norms**	**Results**
Abrasion resistance	ASTM D3884	
Colour fastness to light	AATCC 16E	
Accelerated wear test by sim floor machine	U.S.	
Accelerated soiling	U.S.	
Anti-slip	DIN51130 BGR181	
Water retention	U.S	
Hardness	U.S	
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.251.P.044985.07.09

FIRE TESTING			
	Surface Flammability	ASTM D2859	
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability		• Recyclable material • REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals	

Supermaty.pl