## 123 Polyplush Lite™



- These entrance mats are our top sellers for use in moderate foot traffic.
- Vinyl backing is moisture resistant, slip resistant and will not stain floor.
- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops.
- Vacuum clean.
- Free of toxic DOP and DMF.

## 123 Polyplush Lite™

			PRODUCT SPECIFICATIONS		
Designation		Dust Control Matting			
Description		Absorbent carpet mat			
Material					
Тор		Tufted cut pile carpet made of 100% Polypropylene yarns. 30 grams of yarn per m².			
Backing Black vi		Black vinyl (DOP free)	ack vinyl (DOP free)		
Process		Tufted			
Category		Indoor absorbent - Bestseller			
Recommended use		Indoor - light to medium traffic conditions			
Colours		Brown, Red, Blue, Grey			
Weight		2.4 kg/m²			
Thickness		4.5 mm			
Standard sizes		60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm 90 cm x 20 m 120 cm x 20 m			
Custom sizes		90 cm and 120 cm per linear meter			
Special remarks					
			PRODUCT TESTING		
Tests		ests	Norms	Results	
Abrasion resistance			ASTM D3884		
Colour fastness to ligh		ıt	AATCC 16E		
Accelerated wear test b		by sim floor machine	U.S.		
Accelerated soiling			ASTM 6540		
Anti-slip			DIN51130 - BGR181		
Water retention			ISO 4920 TNO W6034		
Sanitary epidemiologic		c test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV		
Graves tear strength					
Breaking load			ASTM D412		
Elongation					
Hexapod tumble drum tester			ASTM D5252		
			FIRE TESTING		
		Surface Flammability	ASTM D2859	Pass	
		Classification of the reaction to fire performance	DIN EN 13501-1	Efl-S1	
Sustainability			<ul> <li>Recyclable material</li> <li>REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul>		